

ROOF TILES

Tile Range











Thin Flat Tile	
Size	Thickness
420mm x 334mm	21mm
Weight	Minimum Headlap*
4.7kg	75mm (normal exposure)
Minimum Pitch*	Maximum Gauge
100mm headlap - 17.5°	345mm
75mm headlap - 22.5°	Covering Capacity
Cover Width	75mm headlap - 305mm
	9.7 tiles/m²
Weight of Tiling	100mm headlap - 10.5 tiles/m²
75mm headlap - 45kg/m²	Nail Size
100mm headlap - 49kg/m²	40mm x 3.35mm
Batten Size	Aluminium Alloy
50 x 25mm (rafters not exceeding 600mm c/c)	Tiles per Pallet
	228
Tiles per Band	Weight of Pallet
38	1086kg



Duo Thin Flat Tile	
Size	Thickness
420mm x 334mm	21mm
Weight	Minimum Headlap*
4.7kg	75mm (normal exposure)
Minimum Pitch*	Maximum Gauge
100mm headlap - 17.5°	345mm
75mm headlap - 22.5°	Covering Capacity
Cover Width	75mm headlap - 305mm
	9.7 tiles/m²
Weight of Tiling	100mm headlap - 10.5 tiles/m²
75mm headlap - 45kg/m²	Nail Size
100mm headlap - 49kg/m²	40mm x 3.35mm
Batten Size	Aluminium Alloy
50 x 25mm (rafters not exceeding 600mm c/c)	Tiles per Pallet
	228
Tiles per Band	Weight of Pallet
38	1086kg



Round Top Tile	
Size	Thickness
420mm x 334mm	26mm
Weight	Minimum Headlap
4.5kg	75mm
Minimum Pitch	Maximum Gauge
100mm headlap - 17.5°	345mm
75mm headlap - 15°	Covering Capacity
Cover Width	75mm headlap - 305mm
	9.8 tiles/m²
Weight of Tiling	100mm headlap - 10.6 tiles/m²
75mm headlap - 47kg/m²	Nail Size
100mm headlap - 51kg/m²	70mm x 3.35mm
Batten Size	Aluminium Alloy
50 x 25mm (rafters not exceeding 600mm c/c)	Tiles per Pallet
	210
Tiles per Band	Weight of Pallet
35	960kg



Square Top Tile	
Size	Thickness
420mm x 330mm	25mm
Weight	Minimum Headlap
4.6kg	75mm above 25°
Minimum Pitch	Maximum Gauge
100mm headlap - 22.5°	345mm
75mm headlap - 25°	Covering Capacity
Cover Width	75mm headlap - 297mm
	9.8 tiles/m²
Weight of Tiling	100mm headlap - 10.5 tiles/m²
75mm headlap - 45kg/m²	Nail Size
100mm headlap - 49kg/m²	40mm x 3.35mm
Batten Size	Aluminium Alloy
50 x 25mm (rafters not exceeding 600mm c/c)	Tiles per Pallet
	216
Tiles per Band	Weight of Pallet
36	995kg



Only available in Anthracite, Brown and Rustic Red.

Double Roman Tile	
Size	Thickness
420mm x 330mm	25mm
Weight	Minimum Headlap
4.6kg	75mm above 25°
Minimum Pitch	Maximum Gauge
100mm headlap - 22.5°	345mm
75mm headlap - 25°	Covering Capacity
Cover Width	75mm headlap - 297mm
	9.8 tiles/m²
Weight of Tiling	100mm headlap - 10.5 tiles/m²
75mm headlap - 45kg/m²	Nail Size
100mm headlap - 49kg/m²	40mm x 3.35mm
Batten Size	Aluminium Alloy
50 x 25mm (rafters not exceeding 600mm c/c)	Tiles per Pallet
	210
Tiles per Band	Weight of Pallet
35	970kg



Only available in Anthracite, Brown and Rustic Red.

Multi Ridge Tiles

Length x Width

457mm x 250mm

Weight


5kg

Maximum Roof Pitch

45°

Tiles per pallet

140



Hip End Tile

Length

510mm

Width

260mm

Height

130mm

Thickness

25mm

Weight

6.4kg

Colours Available

Anthracite & Terracotta



COLOURS

Available in 5 Colours

Anthracite

Black

Terracotta

Brown


Rustic Red











EMAIL PLANS TO ROOFING@FPMCCANN.CO.UK





✓ 48 Hour lead time on all estimates

✓ All size enquiries welcome, no matter the size

VENTILATION PRODUCTS

Underlay



FP McCann 150gsm Vapour Permeable Membrane

High performance breather membrane
3 layer membrane
Suited for all wind zones
Tested to BS5534:2014 +A2:2018 wind loading
Supplied via partnership with Permavent

Eaves Vent System 6m







Roll Out Rafter Eave Vent
300mm x 6m

Over Fascia Ventilator
10mm or 25mm x6

Felt Support Tray
x10

The Eaves Vent System 6m is available as either a 2 or 3 part system providing a 10mm or 25mm ventilation gap.

DRY FIX SYSTEMS

McCannFast Ridge & Hip Kit 6m



McCannFast Ridge Roll 6m Ventilated or Unventilated

100mm x M5 S/S Screw x10

McCannFast Ridge Union x10

McCannFast Union Clip x10

Ridge Batten Connector x10

Dry Fix Valley System







Eaves Closure Piece

Top Closure Piece 90°

GRP Dry Fix Valley Trough 3m

Minimum Pitch: As per tile profile Maximum Pitch: 60° All components available with a 70mm or 110mm upstand

Dry Verges System





Dry Verges Unit

Multi Ridge End Cap

Tile Fixings











Universal Eave Clip

Sidelock Clip Round Top

Thin Flat Verges Clip

Sidelock Clip Thin Flat

Round Top Verges Clip

McCannVent

Recommended Tile Spacing

5mm gap - 2m centres
10mm gap - 1m centres

Profiles Available

Thin Flat and Round Top

Free ventilation area

10,000mm²

Minimum Pitch

22.5°

Colours Available

Anthracite, Grey, Terracotta, Brown

