

Technical data sheet


SIMPSON

Strong-Tie

FT Frame Tie

When fixing windows, door frames etc. to masonry, the frame tie provides enhanced mortar keying and reduces the risk of injury from sharp edges.

Note: Frame tie should be fully embedded into mortar.



FT
Frame Tie

Technical Data

Product Dimensions

References	Material	Dimensions [mm]				Holes	
		A	B	C	t	Flange C	
						Ø4.1	Ø6
FT150	Galvanised	21.5	100	50	1	2	1
FT200	Galvanised	21.5	150	50	1	2	1
FT250	Galvanised	21.5	200	50	1	2	1
FT150S	Stainless Steel	21.5	100	50	1	2	1
FT200S	Stainless Steel	21.5	150	50	1	2	1
FT250S	Stainless Steel	21.5	200	50	1	2	1

NOTE: not suitable for cavity wall construction

Winchester Road Cardinal Point Tamworth Staffordshire B78 3HG
tel: +44 1827 255600
fax: +44 1827 255616

FT
Frame Tie

Copyright by Simpson Strong-Tie®
Information presented on this document is the exclusive property of Simpson Strong-Tie®
It is valid only when associated with products supplied by Simpson Strong-Tie®

2025-01-24



www.strongtie.co.uk

SIMPSON
Strong-Tie®