

## **Technical Specification**

Product Code: CMA500

Luckinslive 391863820



Description: 45A 1 Gang Double Pole Plate Switch With White Rocker

OFF ON ON General Information		E BUT N () 45A 250V~() BS EN 606589-1 ↓ IN N ()	
Plate Dimensions (mm)	86 (W) x 86 (H) x 9.5 (D)		
Plate Fixing Centres - Horizontal (mm)	60.3		
Style	Rounded Profile		
	Polar White		
Materials	Front Plate: Urea Terminals: Brass	Rear Housing: Urea	eel & Yellow Passivated
	Contacts: Silver "on-lay" Copper / Bra		
	Earth Strap: Mild Steel	internat Dusbars. FO	THEU FIESSEU DIASS
Anti Microbial Certified	Yes		
Operating Voltage (AC)	250	Frequency (Hz)	50
Resistive Load Rating (A)		riequency (Hz)	20
Termination Type	45 Screw		
Terminal Size (mm)	Ø6	Terminal Torque Value (Nm)	2 E
Terminal Capacity - Solid (mm²)	1 x 16	reminal lorque value (NIII)	2.5
Double Pole Switch	Yes		
Twin Earth Terminals	Yes Yes		
	res On & Off		
Product Marking			
Minimum Back Box Depth (mm)	35 IP20		
Ingress Protection Operational Temperature (°C)	-5 to +40		
	- ·		
Warranty (Years)	25		
Standards BS EN 60669-1			

## **Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tarnworth, Staffordshire, B79 7UL United Kingdom **T:** +44 (0)1827 63454 | **F:** +44 (0)1827 63362 **E:** sales@scolmore.com | **W:** scolmore.com









