

Product Code: CMA780


Technical Specification



Description: 13A 2 Gang Switched Socket Outlet With Twin USB (Total 4.2A) Outlets







Terminal Screws: Steel & Yellow Passivated

Internal Busbars: Formed Pressed Brass

Earth Strap: Mild Steel

Terminal Torque Value (Nm) 1.2

General Information

Plate Dimensions (mm) 146 (W) x 86 (H) x 9.5 (D)

Plate Fixing Centres - Horizontal (mm) 120.6

> Style Rounded Profile Colour Polar White

Materials Front Plate & Rocker Switch: Urea Rear Housing: Nylon

> Terminals: Brass Contacts: Silver "on-lay" Copper / Brass

PCB: Mixed Components

Operating Voltage (AC) Frequency (Hz) 50 250

Resistive Load Rating (A)

Anti Microbial Certified

USB Output Type USB Type 'A'

USB Number Of Outputs 2 USB Charging Total Load (A) 4.2 USB Standby Current (mA) USB Charging Voltage (V DC)

Termination Type Screw Terminal Size (mm) Ø5

Terminal Capacity - Solid (mm²) 3 x 2.5 or 2 x 4

Single Pole Switched Yes Twin Earth Terminals

> Product Marking USB 5V 2.1A

Minimum Back Box Depth (mm)

Ingress Protection IP20 Operational Temperature (°C) -5 to +40

> Warranty (Years) Warranty - Electronics (Years) 2

Standards BS 1363-2: 2016 +A1: 2018, BS EN IEC 62368-1, BS EN 62680-1-1

Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

The USB circuits within this socket outlet are designed to withstand insulation resistance tests at 500V.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product. Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All white & grey moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses. All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.

Scolmore House, Mariner, Lichfield Road Industrial Estate, Tamworth, Staffordshire, B79 7UL United Kingdom











Specification is subject to change without notice. Errors & Omissions excluded.