



Product Code: PRC016

Luckinslive 389120258

Description: T2 BC Loop-In Batten Lampholder With H.O. Skirt



**General Information**

|  |                   |                            |                           |
|--|-------------------|----------------------------|---------------------------|
| Dimensions (mm)                              | 86 (Dia) x 80     |                            |                           |
| Colour                                       | Polar White       |                            |                           |
| Materials                                    | Body & Skirt:     | Urea                       | Rear Plate: Polycarbonate |
|  | Internal Housing: | Reinforced Nylon           | Terminals: Brass          |
|  | Terminal Screws:  | Steel & Yellow Passivated  | Springs: Spring Steel     |
| Anti Microbial Certified                     | Yes               |                            |                           |
| Operating Voltage (AC)                       | 250               | Frequency (Hz)             | 50                        |
| Resistive Load Rating (A)                    | 2                 |                            |                           |
| Termination Type                             | Screw             |                            |                           |
| Terminal Size (mm)                           | Ø3,5              | Terminal Torque Value (Nm) | 0,5                       |
| Terminal Capacity - Solid (mm <sup>2</sup> ) | 2 x 1,5           |                            |                           |
| Ingress Protection                           | IP20              |                            |                           |
| Operational Temperature (°C)                 | -5 to +40         |                            |                           |
| Warranty (Years)                             | 10                |                            |                           |

**Standards** BS EN 61184, BS 67

**Additional Information**

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
 Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
 Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.  
 Facility to loop in and out.  
 All white moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.  
 All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.



Catalogue



Range



DoC

