



H2 Lite

TRIAC Dimmable, fire-rated downlight with integrated bezel & Easy-fit connector

Features		Installation Information	
IP rating	IP65 (from below) IP20 (from above)	Input	220-240V AC
CSP Switchable	Single CCT	Maximum Ambient Temperature	40°C
Tiltable	No	Weight	180g
UGR	UGR<22	Insulation Coverable	Rolled and blown insulation
Sensor Option	Smart Microwave	Inrush Current	1.3A 0.23ms
Dimmable Option	Yes (Mains)	Cut Out Size	64-72
LED Lifetime	L70 70,000h	Construction Material	Mild steel / VO rated plastic
Colour Rendering Index	CRI>80	UK Bathroom Zone	1
Colour Consistency	SDCM4	Maximum ceiling thickness	40 mm
Emergency Option	No	SELV	Yes
Rotation Angle	No	Electric Class (1, 2, 3)	2
		Suitable for coastal areas	No
		Install Connector Type	Easy-fit connector
		UK Building Regulations	Part B, C, E, P & L
		Part B Fire Rating	Solid Timber 30/60/90min, I-Joist 30min, Metal Web 30min
		Power Factor	0.80

Photometrics @ 25°C

Product Code	Finish	Type	W	Colour	Beam	lm	lm/W	Lx @ 1m	Energy
DLT388BS5540	Brushed steel	Single unit	4.3W	4000K	55°	490	114	440	
DLT388BS5530	Brushed steel	Single unit	4.3W	3000K	55°	460	107	413	
DLT388MW5540	Matt white	Single unit	4.3W	4000K	55°	490	114	440	
DLT388MW5530	Matt white	Single unit	4.3W	3000K	55°	460	107	413	
DLT388BLK5540	Matt black	Single unit	4.3W	4000K	55°	490	114	440	
DLT388BLK5530	Matt black	Single unit	4.3W	3000K	55°	460	107	413	

Product not suitable for exterior use, please use H2 Pro Extreme. Energy rating is a reflection of the LED light source.

Wiring Information

Cable / Flying Lead	0.15m
Cable Required for Connector	Push-fit terminal for: Twin & Earth (6242Y 2x1.5mm²) or 3-core cable (R02V 3x1.5mm²)
Type of Wiring Required	Parallel
Input Cable Type	H03VVH2-F (2 CORE 0.75MM)

LED Driver

Driver	Input	SELV	Dimming	Bathroom Zone	Min	Max
N/A (integrated SELV driver)	220-240V	Yes	Yes (mains)	1 (Ceiling only)	N/A	N/A

Accessories

DLCONVERT70	Converter plate	Sold Separately
DM298GRID	LED mains grid dimmer	Sold Separately
DM298FP	Faceplate dimmer	Sold Separately
DLCVT110	Converter Plate	Sold Separately



- Patented Easy-fit connector for first & second fix
- Shallow depth 46mm
- Insulation coverable

Guarantee

Warranty 10 years

Features & benefits

- With approximately 5 million units supplied to a wide range of customers, H2 Lite has a proven history of excellent performance, fast installation and lifetime you can trust
- Unique product design with a new shallow depth to enable use in the smallest of ceiling voids
- TRIAC mains dimmable, works with leading & trailing edge dimmers
- Optimised design with no waste, minimizing the use of materials and impact on the planet
- FSC certificated packaging ensure minimal waste
- When using a converter plate, the IP rating is not affected; however, the product is no longer fire-rated.

Patent Information

GB2576385 EP3648256 HK40014447

