



The >B< Press range is an innovative press system which guarantees both a secure joint and a quick and simple installation.

#### Features and Benefits:


























- Available in copper and red brass fittings.
- Compatible with various press tools and jaws.\*
- >B< Press is quick and simple to install, saving time and money.
- Flame free installation for ensuring on site safety.
- >B< Profile 3 point press ensures a leak free, secure and permanent joint.
- Available in 15mm to 108mm.
- Suitable for use with hard, half-hard and soft copper tubes to EN 1057.
- Manufactured and designed to BS 8537 copper tube press fittings.
- Designed with a mechanical hexagonal press form which indicates fittings has been secured ensuring no joint rotation.
- >B< Press has a high quality O-Ring material that forms a secure leak free joint when pressed.\*
- Leading edge design ensures the chances of damaging the O-Rings are reduced during installation.

\*Please see compatibility list on website for more details

\*Only available on sizes 15-54mm



## >B<Press Copper Range with Press Indicators

<b>Straight Coupler</b>  <b>P1 (P5270)</b> From: 15mm To: 108mm	<b>Reduced Straight Coupler</b>  <b>P1R (P5240)</b> From: 22 x 15mm To: 54 x 42mm	<b>Slip Coupler</b>  <b>P1S (P4275)</b> From: 15mm To: 108mm	<b>Female Straight Connector</b>  <b>P2 (P4270G)</b> From: 15 x 1/2" To: 54 x 2"	<b>Male Straight Connector</b>  <b>P3 (P4243G)</b> From: 15 x 1/2" To: 76 x 3"	<b>90° Elbow</b>  <b>P12 (P5002)</b> From: 15mm To: 54mm
<b>90° Elbow</b>  <b>P12 (4090)</b> From: 67mm To: 108mm	<b>90° Street Elbow</b>  <b>P12S (P5001)</b> From: 15mm To: 54mm	<b>90° Street Elbow Gunmetal</b>  <b>P12S (P4092)</b> From: 67mm To: 108mm	<b>Fitting Reducer</b>  <b>P6 (P5243)</b> From: 15 x 12mm To: 108 x 89mm	<b>90° Bend with Male Thread</b>  <b>P13 (P4001G)</b> From: 15 x 1/2" To: 54 x 2"	<b>90° Elbow with Female Thread</b>  <b>P14 (P4090G)</b> From: 15 x 1/2" To: 54 x 2"
<b>Return Bend</b>  <b>P20 (P5060)</b> Size: 22mm	<b>45° Obtuse Elbow</b>  <b>P21 (P5041)</b> From: 15mm To: 108mm	<b>45° Obtuse Street Elbow</b>  <b>P21S (P5040)</b> From: 15mm To: 108mm	<b>Tee Equal</b>  <b>P24 (P5130)</b> From: 15mm To: 108mm	<b>Tee Reduced Branch</b>  <b>P25 (P5130)</b> From: 22 x 22 x 15mm To: 108 x 108 x 89mm	<b>Tee Reduced End</b>  <b>P26 (P5130)</b> From: 22 x 15 x 22mm To: 28 x 22 x 28mm
<b>Tee Reduced End &amp; Branch</b>  <b>P27 (P5130)</b> From: 22 x 15 x 15mm To: 54 x 42 x 42mm	<b>Reduced Both Ends</b>  <b>P28 (P5130)</b> From: 15 x 15 x 22mm To: 22 x 22 x 28mm	<b>Tee with Female Threaded Branch</b>  <b>P30 (P4130G)</b> From: 15 x 15 x 1/2" To: 108 x 108 x 2"	<b>Male Straight Union Connector</b>  <b>P69M (P6917)</b> From: 15 x 1/2" To: 54 x 2"	<b>Female Straight Union Connector</b>  <b>P69F (P4330G)</b> From: 15 x 1/2" To: 54 x 2"	<b>PN16 Flange (4/8 hole)</b>  <b>P4230B</b> From: 67mm To: 108mm
<b>Stop End</b>  <b>P61 (P5301)</b> From: 15mm To: 108mm	<ul style="list-style-type: none"> <li>Specifically designed EPDM O-Ring making &gt;B&lt; Press suitable for applications including HVAC, compressed air and potable water applications.</li> <li>Available in sizes 15 – 108mm.</li> <li>Designed for hydrostatic water pressure up to 16 bar.</li> <li>Designed for temperature ranges of -35°C to 110°C.</li> <li>Fully tested to 64 bar pressures and approved by WRAS, KIWA and DVGW.</li> <li>Patented design.</li> </ul>				