



Product

INOX-PRO Stainless Steel Shock Arrestors


- Z1-300016SSD - 0.16L INOX-PRO Shock Arrestor 1/2" Connection Brushed Finish**
- Z1-300016SS14 - 0.16L INOX-PRO Shock Arrestor 1/4" Connection Brushed Finish**
- Z1-300050SSD - 0.5L INOX-PRO Shock Arrestor 1/2" Connection Brushed Finish**
- Z1-300016SSNO - 0.16L INOX-PRO Shock Arrestor 15mm Connection Polished Finish**
- Z1-300050SS - 0.5L INOX-PRO Shock Arrestor 1/2" Connection Polished Finish**

Technical Specification

Operating Temperatures:	-10°C - 99°C
Max Working Pressure:	15 Bar
Pre Charge Pressure:	3.5 Bar
Shell:	304 Grade Stainless Steel
Connection:	Stainless Steel
Membrane:	Butyl

Dimensions

Code	Capacity (Litres)	Diameter Ø(mm)	Height H(mm)	Connection ØC(BSP)
Z1-300016SSD	0.16L	82	72	1/2" G
Z1-300016SS14	0.16L	82	72	3/4" G
Z1-300050SSD	0.5	94	119	1/2" G
Z1-300016SSNO	0.16L	82	72	15mm Comp
Z1-300050SS	0.5	94	119	1/2" G



Additional Information

Prevents water hammer effect in water systems, solving vibration and noises issues.

Ideal for installations where hygiene is at a premium

5 years warranty

100% factory tested

Suitable for potable applications

Fully certified according to the pressure equipment directive 2014/68/EU

Typical Installations

