Technical Data Sheet



AGB2XT25WC(FINISH) ATLANTIC® AGB POLARIS 2XT MAGNETIC BATH LOCK - 35MM BACKSET

Product Code AGB2XT25WC(finish)

Product Name ATLANTIC® AGB Polaris 2XT Italian Magnetic Bathlock - 35mm Backset **Product Description** ATLANTIC® AGB Polaris 2XT Italian Magnetic Bolt Through Bathroom Lock with

Adjustable Strike Plate - Sold in Singles - 35mm Backset

Product Base Material Zamak, Steel

Available Finishes & Backset AGB2XT25WCMB (Matt Black)

AGB2XT25WCPC (Polished Chrome)

Other Information To be cleaned using a soft damp cloth. Chemicals, solvents or abrasives will


damage the applied finish.

10 Year Mechanical Guarantee subject to fitting requirements.

Sold with matching wood screws.

Dimensions

Lock body 132x60 Backset 35mm



Product Image



Polished Chrome (PC)

Care of Finish

In the unusual event of this product failing mechanically, we will replace it free of charge, providing you can supply us with the faulty product and a receipt to show proof of purchase. If the items are not fitted in accordance with the fitting instructions, in a correct application, this may not apply.

Products have an applied finish, and we do recommend regular cleaning with a soft cloth. If necessary, you may moisten the cloth, with water. If this is not effective in removing accumulated deposits, try using a PH-neutral soap on a soft cloth, then remove the soap immediately after application, with the help of a clean, moist, soft cloth. Under no circumstances should you use an abrasive/hard tool, chemical, acidic or abrasive substance to clean these products. This will break down the applied finish. The finish may chip or scratch if subjected to impact from sharp items such as keys and jewellery. Atlantic UK retains the right to send items away for chemical testing to analyse if the product has come into contact with any abrasive or chemical substance before issuing replacements.

Please be aware that in environments where there are high concentrations of chemicals in the air, for example from the use of low-quality paint or corrosive agents, corrosion and damage may occur to the surface of the product. Products should therefore not be fitted in such environments, until the high concentration of chemicals in the air has subsided.