

Fitting Instructions – Atlantic Magnetic Latch 3”

ML3SN

Date Modified: 10/08/2022

Last modified by: Alice W

For best results when fixing a magnetic latch follow these instructions.

Atlantic recommends this product is fitted by a joiner.

Before beginning installation, check the product is as required/ordered.

You will also require a combination square or steel ruler.

Separate out all components supplied as follows:

X1 Magnetic Latch

X1 Dust box (must use included)

X1 Strike Plate

X4 Screw

- 1) First, mark out the desired position of the latch on the leading edge of the door.
- 2) Then, router mortice for the latch body.
- 3) Using the latch, mark out the spindle backset.
- 4) Insert the latch into the mortice. Ensuring that orientation is correct (see latch icon).
- 5) When the latch is inserted into the door, mark out for the face plate.
- 6) Then, rebate out for the face plate.
- 7) Now, fix the latch into the door using X2 of the screws provided.
- 8) Using a combination square, measure across from the center of the latch to the edge of the door.
- 9) Transfer the dimension into the desired position on the door frame.
- 10) Mark out the dust box and strike plate.
- 11) Now, router out for the dust box and rebate out for the strike plate.
- 12) Finally, fix in place using X2 screws provided.
- 13) Close the door to ensure the latch functions as desired.