Technical Data Sheet



OE178WC(finish) OLD ENGLISH® WARWICK ON BACKPLATE - WC TURN

Product Code OE178WC(finish)

Product Name OLD ENGLISH® Warwick Lever on Backplate - WC Turn & Release

Product Description Warwick Lever on Backplate - WC Turn & Release

Product Base Material Zinc Allov

Available Finishes Antique Brass (AB) Urban Dark Bronze(UDB)

> Distressed Silver (DS) Matt Black (MB)

Mall Anlique Brass (MAB) Mall Gun Melal (MBN)

Other Information To be cleaned using a soft damp cloth. Chemicals, solvents or abrasives will

damage the applied finish.

Supplied 2 x Bolt through Fixing, Wood Screws, 8 mm x 8 mm x 100 mm Split Spindle, 2 x Loctite coated Grub Screws & Allen Key, Bolt through Fixing and Grub Screws must be used. 10 Year Mechanical Guarantee subject to filling

requirements. Suitable for 35mm doors only. For use with sashlocks only.

Matching Latch Lever: OE178L(finish) Malching Key Lever: OE178K(finish)

Dimensions

OE178WC Lever Dimensions: Backplate width: 51mm Handle length: 121mm Backplate Length: 175mm Backplate Depth: 10mm

Backplate & Lever Projection: 62mm



Care of Finish

in the unusural event of this product failing mechanically, we will replace in the unusural event of this product failing mechanically, we will replace in the unusural event of this product failing mechanically, we will replace in the unusural event of this product failing mechanically, we will replace in the unusural event of this product failing mechanically, we will replace in the unusural event of this product failing mechanically, we will replace in the unusural event of the unusural event of this product failing mechanically, we will replace in the unusural event of this product failing mechanically, we will replace in the unusural event of the u proof of purchase. If the items are not fitted in occordance with the fitting instructions, in a correct application, this may not apply.

Products have an applied linish, one we da recammene regular cleaning with a soft cloth. If necessary, you may moisten the cloth, with water. If his is not a feetive in removing accumulated deposits, try using a Pt-neutral scap on a soil cloth, then remove the scap immediately after application, with the help of a clean, moist, soft cloth. Under no dircumstances should you use an abrasive/hard tool, chemical, adicid or obrasive substance to clean these products. This will break down the applied finish. The Enish may onlip or social diditious jedled to impact from sharp items such as keys and jewellery. Attanta UK retains the right to send from away for chemical lesting to analyse it the product has come in o contact with any abrasive or chemical substance before issuing replacements.

Please be aware that in environments where there are nigh concentrations of chemicals in the air, for example from the use of low quality paint or corrosive agents, conosion and damage may occur to the surface at the product. Products should therefore not be 7, each environments, until the high concentration of chemicals in the air has subsided.