Technical Data Sheet



A2HB32525(finish) ATLANTIC® BALL BEARING HINGE

Product Code A2H32525(finish)

Product Description

Available Finishes

Product Base Material

Product Name ATLANTIC® Ball Bearing Hinge

3" Ball Bearing Hinge - 3" x 2.5" x 2.5mm with Screws

Steel

Antique Brass (AB)

Polished Chrome (PC)

Black Nickel (BN)

Polished Brass (PB)

Distressed Silver (DS)

Satin Chrome (SC)

Matt Antique Brass (MAB)

Satin Nickel (SN)

Matt Black (MB)

Matt Gun Metal (MBN)

Other Information To be cleaned using a soft damp cloth. Chemicals, solvents or abrasives will


damage the applied finish. Supplied with wood screws.

10 Year Mechanical Guarantee subject to fitting requirements.

Matching Hinges: AWH3222(finish), AH1433(finish), APH424(finish)

Dimensions

Length (C): 75mm Full Width (A): 63mm Depth of Leaf(D): 2.5mm Depth of Knuckle(E): 10mm





Care of Finish

In the unusual event of this product failing mechanically, we will replace it free of charge, providing you can supply us with the faulty product and a receipt to show proof of purchase. If the items are not fitted in accordance with the fitting instructions, in a correct application, this may not apply.

Products have an applied finish, and we do recommend regular cleaning with a soft cloth. If necessary, you may moisten the cloth, with water. If this is not effective in removing accumulated deposits, try using a PH-neutral soap on a soft cloth, then remove the soap immediately after application, with the help of a clean, moist, soft cloth. Under no circumstances should you use an abrasive/hard tool, chemical, acidic or abrasive substance to clean these products. This will break down the applied finish. The finish may chip or scratch if subjected to impact from sharp items such as keys and jewellery. Atlantic UK retains the right to send items away for chemical testing to analyse if the product has come into contact with any abrasive or chemical substance before issuing replacements.

Please be aware that in environments where there are high concentrations of chemicals in the air, for example from the use of low-quality paint or corrosive agents, corrosion and damage may occur to the surface of the product. Products should therefore not be fitted in such environments, until the high concentration of chemicals in the air has subsided.