

ATLANTIC® AGB SLIDING DOOR ROUND FLUSH HANDLE

Product Code	See below
Product Name	ATLANTIC® AGB Sliding Door Round Flush Pull Handle
Product Description	ATLANTIC® AGB Sliding Door Round Flush Pull Handle to suit Ermetika Pocket Doors
Product Base Material	Steel
Available Finishes	Matt Black (MB) - B019201093 Polished Brass (PB) - B019201003 Satin Chrome (SC) - B019201032
Other Information	To be cleaned using a soft damp cloth. Chemicals, solvents or abrasives will damage the applied finish. 10 Year Mechanical Guarantee subject to fitting requirements. Sold with matching wood screws.

Dimensions

Inside of Pull: 45.5mm
Diameter of rear of Pull: 48mm
Overall Pull diameter: 60mm
Depth of Finger Pull: 24mm
Inside of Finger Pull: 19mm
Overall diameter of Finger Pull: 25mm

Please see next page for further dimensions.

Product Image



Product Finish
Pictured: Satin Chrome

Care of Finish

In the unusual event of this product failing mechanically, we will replace it free of charge, providing you can supply us with the faulty product and a receipt to show proof of purchase. If the items are not fitted in accordance with the fitting instructions, in a correct application, this may not apply.

These latches have an applied finish, and we do recommend regular cleaning with a soft cloth. If necessary, you may moisten the cloth, with water. If this is not effective in removing accumulated deposit, try using a PH neutral soap on a soft cloth, then remove soap immediately after application, with the help of a clean, moist, soft cloth. Under no circumstances should you use an abrasive/hard tool, chemical, acidic or abrasive substance to clean these locks. This will break down the applied finish. The finish may chip or scratch if subjected to impact from sharp items such as keys and jewellery. Atlantic UK retain the right to send items away for chemical testing to analyse if the product has come into contact with any abrasive or chemical substance before issuing replacements.

Please be aware that environments where there are high concentrations of chemicals in the air, for example from use of low quality paint or corrosive agents, corrosion and damage may occur to the surface of the lock. Locks should therefore not be fitted in such environments, until the high concentration of chemicals in the air have subsided.

the finish matters