## **Technical** Data Sheet



## OERKE(finish) OLD ENGLISH® OPEN KEY ESCUTCHEON

Product Code

Product Name

**Product Description** 

Product Base Material

Available Finishes

OERKE(finish)

Old English® Open Key Escutcheon

Escutcheon to suit Old English® Mortice Knobs with Open Key - profile keyhole

Solid Brass

Antique Brass (AB) Polished Chrome (PC) Antique Copper (AC) Polished Nickel (PN) Black Nickel (BN) Satin Brass (SB) Distressed Silver (DS) Satin Chrome (SC) Matt Antique Brass (MAB) Satin Nickel (SN)

Matt Black (MB) Urban Bronze (UB)

Matt Gun Metal (MBN) Urban Satin Coper (USC)

Polished Brass (PB)

Other Information To be cleaned using a soft damp cloth. Chemicals, solvents or abrasives will

damage the applied finish. Supplied 2 x Bolt through Fixing, Wood Screws,

1 x Loctite coated Grub Screws & Allen Key. Bolt through Fixing and Grub Screws must be used.

10 Year Mechanical Guarantee subject to fitting requirements.

**Dimensions** Diameter: 42mm Unit: Sold in pairs

Product Image



Finish Photographed: Matt Gun Metal

## Care of Finish

In the unusual event of this product failing mechanically, we will replace it free of charge, providing you can supply us with the faulty product and a receipt to show proof of purchase. If the items are not fitted in accordance with the fitting instructions, in a correct application, this may not apply.

Products have an applied finish, and we do recommend regular cleaning with a soft cloth. If necessary, you may moisten the cloth, with water. If this is not effective in removing accumulated deposits, try using a PH-neutral soap on a soft cloth, then remove the soap immediately after application, with the help of a clean, moist, soft cloth. Under no circumstances should you use an abrasive/hard tool, chemical, acidic or abrasive substance to clean these products. This will break down the applied finish. The finish may chip or scratch if subjected to impact from sharp items such as keys and jewellery. Atlantic UK retains the right to send items away for chemical testing to analyse if the product has come into contact with any abrasive or chemical substance before issuing replacements.

Please be aware that in environments where there are high concentrations of chemicals in the air, for example from the use of low-quality paint or corrosive agents, corrosion and damage may occur to the surface of the product. Products should therefore not be fitted in such environments, until the high concentration of chemicals in the air has subsided.

the finish matters