



For oiling bare wood

Quicker drying than Raw Linseed Oil



Boiled Linseed Oil

Ideal for oiling bare wood, adding to paint, and softening Metal Glazing Putty. Will waterproof ground sheets and tarpaulins.

IMPORTANT

Application cloths and soiled cleaning rags may self-ignite without warning. Dispose of safely to avoid fire risks. Lay out flat in single layers to dry or wash out well in warm soapy water before disposal.

HEALTH & SAFETY

Keep out of reach of children. Do not get in eyes, on skin, or on clothing. Wear protective gloves.

IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

IF ON SKIN: Gently wash with plenty of soap and water.

IF IN YES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

HEI: H5EP-G31.I-H01N-MΔ95

Please refer to Product Data Sheet for full information at





300mle

For information on Rustins' products visit our website at www.rustins.co.u.k or contact us at Rustins Ltd, Waterion Road, London, NW2 7TX United Kingdom rustins@rustins.co.u.k Telephone: +44 (0)20 8450 4666 R0I: Excellence Ltd, 43 Grange Parade, Dublin D13 Y860 Ireland. TEI: +333 1 - 332 3300