



## **SPECIFICATION SHEET**

**Product Code** 

VP\*411#

Description

10AX 1 Gang 2 Way Switch 'Ingot' (Modular)





88mm x 88mm x 8mm (Excluding Gasket)
Replace * with: AB (Antique Brass), BN (Black Nickel), BR (Polished Brass),
CH (Polished Chrome), PN (Pearl Nickel), SB (Satin Brass), SC (Satin
Chrome), and SS (Stainless Steel).
Replace # with: WH (White) and BK (Black).
Black or White gasket supplied to match appropriate inserts.
(Antique Brass and Black Nickel are only available with back inserts).
Rear Housing: Nylon
Front Plate: Stainless Steel
Terminals: Brass
Earth Strap: Mild Steel
Terminal Screws: Steel and Yellow Passivated
Silver "on-lay" copper/brass contacts.
16mm – 47mm
4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup>
Live: 3.5mm
Earth: 3.5mm
10AX (Suitable for Inductive loads)
Yes
1
Yes
No
10 Years Domestic

Standards	BS EN 60669
Additional Information	Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product.  Bare earth cables must always be covered with appropriate sleeving and
	wired to the earth terminal.  Interchangeable with switches in the MiniGrid system.

V1.0