

## SPECIFICATION SHEET

Product Code MD002\*

Description 10AX 2 Way Switch Module



| General Information  |   |
|----------------------|---|
| Finishes Available   | Replace * with: WH (White), BK (Black), PW (Polar White), CH (Chrome), SC (Satin Chrome), BR (Brass), BN (Black Nickel), PN (Pearl Nickel), AB (Antique Brass), SB (Satin Brass), BS (Brushed Steel), and SS (Stainless Steel). |
| Dimensions           | Module Width: 16mm, Rocker Height: 31.5mm   |
| Terminal Size        | Live 3.5mm Diameter   |
| Material composition | Rear Housing: Nylon<br>Rocker: Urea or Urea + Stainless Steel Cover<br>Terminals: Brass<br>Terminal Screws: Steel and Yellow Passivated<br>Silver "on-lay" copper/brass contacts.   |
| Back Box Depth       | 16mm – 47mm   |
| Cable Size           | 4 x 1.5mm <sup>2</sup> or 2 x 2.5mm <sup>2</sup> or 1 x 6mm <sup>2</sup>  |
| Warranty             | 10 Years domestic   |

| Standards | BS EN 60669 |
|-----------|-------------|
|-----------|-------------|

| Additional Information | <p>Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram supplied with the relevant product.</p> <p>These products are rated at 10A; therefore all terminals should not exceed the stated amperage.</p> <p>Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.</p> <p>All white and anthracite grey moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases. All products independently tested achieved a 99.9% kill rate across all four types of the strains of bacteria – MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae</p> |
|------------------------|---|
|------------------------|---|