

Data sheet

Part No.

SFR

Description

distribution and outlet box, rounded edges
for surface installation, mounting screw spacing 60mm, threadsize M 3.5mm, lugs with brass inserts, knock-outs for 1 conduit and 1 trunking entry

Colour

white, similar to RAL 9010

Standard: EN 60670, BS 4662

PVC-LSF 



Working temperature		Material		
-5 to +60°C		PVC-U		
Art. no.	Dimensions	Number of units	PU	PU
103 221 SFR 1/32	32 mm	1	10 pc	180 pc
103 223 SFR 2/32	32 mm	2	10 pc	120 pc
103 225 SFR 1/44	44 mm	1	10 pc	120 pc
103 227 SFR 2/44	44 mm	2	10 pc	80 pc

For sale in the UK market only.

All figures refer to standardised test samples and are given to our best knowledge but without further commitment. It is Univolt's belief that information set forth in this Data Sheet is accurate, Univolt, Dietzel GmbH, 1110 Wien, 1. Haidequerstraße 3-5, www.dietzel-univolt.com, makes no warranty, expressed or implied, with respect thereto and disclaims any liability from reliance thereon. All data are subject to change without prior notice. Fully responsible for the content: UNIVOLT (UK) Ltd. A1 Connect Unit 2, Cole Green Lane, AL7 4FW Welwyn Garden City.