



### General Information

|  |  |   |
|--|--|---|
| Dimensions (mm)                              | 86 (Dia) x 30  |   |
| Colour                                       | Polar White  |   |
| Materials                                    | Cover, Body & Skirt: Urea<br>Terminals: Brass<br>Cable Type: 2G H05V2V2-F<br>Springs: Spring Steel | Rear Plate: Polycarbonate<br>Terminal Screws: Steel & Yellow Passivated<br>Internal Housing: Reinforced Nylon |
| Operating Voltage (AC)                       | 250  | Frequency (Hz) 50   |
| Resistive Load Rating (A)                    | 2  |   |
| Pre-wired Cable Specification                | 2G 0.75mm <sup>2</sup> H05V2V2-F   |   |
| Termination Type                             | Screw  |   |
| Terminal Size (mm)                           | Ø3.5   | Terminal Torque Value (Nm) 0.5  |
| Terminal Capacity - Solid (mm <sup>2</sup> ) | 2 x 1.5  |   |
| Ingress Protection                           | IP20   |   |
| Operational Temperature (°C)                 | -5 to +40  |   |
| Warranty (Years)                             | 10   |   |

**Standards** BS EN 61184, BS 67

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.  
Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.  
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.