



### General Information

Dimensions (mm)	86 (Dia) x 30	
Colour	Brown	
Materials	Body: Urea Terminal Screws: Steel and Yellow Passivated	Earth Terminals: Brass
Anti Microbial Certified	Yes	
Operating Voltage (AC)	250	Frequency (Hz) 50
Resistive Load Rating (A)	20	
Number Of Terminals	6	
Termination Type	Screw	
Terminal Size (mm)	3.6 x 7	Terminal Torque Value (Nm) 0.8
Terminal Capacity - Solid (mm²)	4 x 15	
Entry Knockout Dimensions (mm)	11.8 x 7 (x4)	
Ingress Protection	IP20	
Operational Temperature (°C)	-20 to +55	
Warranty (Years)	10	

**Standards** BS EN 60670-1, BS EN 60670-22

### Additional Information

For cleaning / polishing of products, use only a soft, dry, clean cloth.

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.

Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.

All moulded accessories are manufactured using Urea Formaldehyde, which has similar inherent properties to antimicrobial additives that inhibit the growth of infectious diseases as well as anti-viral properties against enveloped and non-enveloped viruses.

All products have been independently tested with 99.9% of enveloped viruses and 92% of non-enveloped viruses killed off whilst achieving a 99.9% kill rate across all four types of the strains of bacteria - MRSA, E-Coli, Salmonella, and Klebsiella Pneumoniae.