



## Product Information

|                      |                                    |
|----------------------|------------------------------------|
| Ibstock Code         | A4027A                             |
| Type                 | Stock                              |
| Facing Description   | Sandfaced                          |
| Dry Brick Weight     | 2.2kg                              |
| Pack Quantity        | 500                                |
| Packaging (standard) | Banded (Plastic)                   |
| Factory              | Ashdown                            |
| EPD                  | Ashdown Product Group 2 (HUB-6076) |

## Technical Specification (to BS EN 771-1)

|                                                       |               |
|-------------------------------------------------------|---------------|
| Brick Dimensions (L x W x H mm)                       | 215x102x65    |
| Size Tolerances Mean & Range                          | T1 R1         |
| Configuration                                         | Single Frog   |
| Voids (%)                                             | 10-15%        |
| Compressive Strength (N/mm²)                          | 30            |
| Active Soluble Salts                                  | S2            |
| Water Absorption (% weight)                           | 15            |
| Durability                                            | F2            |
| Gross Dry Density (kg/m³)                             | 1610          |
| Equivalent Thermal Conductivity "K" value 5% Exposed  | 0.86          |
| Initial Rate of Absorption (Suction Rate) (kg/m²/min) | 1.9           |
| EAN                                                   | 5036335024775 |