Handy Pack 44.

November 2023 | Data Sheet





Superglass Handy Pack 44 is a non-combustible glass mineral wool insulation roll. The roll is supplied in shorter roll length for ease of handling and partially perforated providing the flexibility to be used between common joists spacings and as uncut as a full width roll as layers over the joists, reducing the need for on-site cutting and waste.

Application.

Superglass Handy Pack 44 is primarily used as thermal insulation between and over the timber joists of new and existing lofts/cold pitched roofs. However, it can be used in several other applications including suspended timber grounds floors.

Performance.

Thermal Conductivity:

Declared thermal conductivity (lambda (λ) value) of 0.044W/mK.

Fire Classification:

Deemed non-combustible with a fire classification of Euroclass A1 (the highest possible rating) when tested to BS EN 13501-1 Reaction to Fire.





Typical applications:

New and existing lofts/cold pitched roofs.







Noncombustible



Easy to Install



Recycled Content



Handy Pack 44. Technical Characteristics.

Product Specification.

Thickness (mm)	Length (m)	Width (mm)	Pack Area (m²)	Packs per pallet	Thermal Conductivity (W/mK)	Thermal Resistance (m²K/W)	Product Code
100	7.00	1140/2x570/3x380	7.980	30	0.044	2.25	5780

Please note that all dimensions are nominal.

Additional Information.

Vapour Resistivity

The product has a nominal vapour resistivity of 5 MN·s/g·m.

Environmental credentials.

- Manufactured in accordance with ISO 14001 Environmental Management Systems (EMS). Certificate number: EMS 646508
- Contains no ozone-depleting substances or greenhouse gases.
 For more information, please refer to the Environmental Product Declaration (FPD)
- Made from up to 84% recycled glass.
- Generic BRE Green Guide Rating of A+.

Standards and Approvals.

Manufactured in accordance with:

- BS EN 13162:2012(+A1:2015) Thermal insulation products for buildings - Factory made mineral wool (MW) products.
- BS EN 13172: 2012 Thermal insulation products Evaluation of conformity.
- BS EN ISO 9001 Quality Management Systems (QMS).
 Certificate number: FM 02264.

Certifications.

- UKCA certified to BS EN 13162:2012+A1:2015.
 Certificate number: 0086 CPR 469699.
- CE marked to BS EN 13162:2012+A1:2015.
 Certificate number: 0751-CPR-399.0-01.

A copy of the product Declaration of Performance (DoP) can be downloaded from the Superglass website.

Handling & Storage.

Due to its physical characteristics, Handy Pack 44 is quick and easy to handle and install.

The product is supplied compression packed in polythene to provide short term protection only. For long term protection, the product must be stored indoors, or under a waterproof covering and off the ground to protect from weather damage. The product should not be left permanently exposed to the elements.

All Superglass products are non-hygroscopic, will not rot, degrade, or sustain vermin and will not encourage the growth of mould, bacteria, or fundi.

















Superglass Insulation Limited. Thistle Industrial Estate, Kerse Road, Stirling, Scotland FK7 7QQ

Technical

Hotline: 0808 1645 134
Email: technical.stirling@etexgroup.com

Customer Services
Tel: 01786 451170

 ${\it Email:} \textbf{ customerservice.stirling@etexgroup.com}$

Social

- www.facebook.com/superglassinsulationuk
- in www.linkedin.com/company/superglassuk/
- f www.twitter.com/Superglass_UK