

by **timloc**

Felt Support Tray

Designed to prevent damage to roofing felt

Use

- At the eaves of a roof to support and protect roofing felt
- For remedial work to replace worn or perished roofing fel

Features and Benefits

- Effective, quick and easy to fit
- Improves performance of other roofing materials
- · Ideal for remedial work
- Durable and totally resistant to decay
- Supplied in convenient 1.5m lengths or 600mm

Quality

- Satisfies all NHBC requirements
- Manufactured to BS EN ISO 9001 and BS EN ISO 14001
- Complies with all relevant Building Regulations
- Meets all relevant British Standards

Material and Colour Choice

- Extruded in UPVC
- Available in black/dark grey

Installation Advice

- Fit on the top of the fascia board below roofing felt, allowing a 150mm overlap where pieces join
- Secure with clout nails and fold back the rear flap to rest on the rafters

How to Order

 Measure the overall length of the eaves to be protected and divide by 1.35m to determine the number of protectors required or 450mm (1128)



Bill of Quantity

G20 Carpentry/Timber Framing/First Fixing

Clause

900^ EAVES SOFFIT VENTILATION

- Manufacturer: Timloc Building Products, Timloc House, Ozone Park, Howden, East Yorkshire, DN14 7SD. T: 01405 765567 W: www.timloc.co.uk
- Product Reference: 3017
- Type: Protector (1500mm)
- Colour: Black

Product Codes

Description	Pack Quantity	Product Code
Felt support tray 1500mm	10	3017
Felt support tray 600mm	20	1128

Product Dimensions





