



## Product Information

|                        |                                  |
|------------------------|----------------------------------|
| Ibstock Code:          | A0102A                           |
| Type:                  | Stock                            |
| Facing Description:    | Sandcreased                      |
| Dry Brick Weight (kg): | 2kg                              |
| Pack Quantity:         | 430                              |
| Packaging (standard):  | Banded (Plastic) and Stretchwrap |
| Factory:               | Leicester                        |

## Technical Specification (to BS EN 771-1)

|   |             |
|---|-------------|
| Brick Dimensions (L x W x H mm):                                    | 215x102x65  |
| Size Tolerances Mean & Range:                                       | T2 R1       |
| Configuration:  | Single Frog |
| Voids (%):  | 8-13%       |
| Compressive Strength (N/mm <sup>2</sup> ):                          | 15          |
| Active Soluble Salts:   | S2          |
| Water Absorption (% weight):  | 25          |
| Durability:   | F2          |
| Gross Dry Density (Sound Insulation) (Kg/m <sup>3</sup> ):          | 1310        |
| Equivalent Thermal Conductivity "K" value 5% Exposed:               | 0.65        |
| Initial Rate of Absorption (Suction Rate) (Kg/m <sup>2</sup> /min): | 3           |
| EAN:  | 5.04E+12    |