


## PRODUCT DESCRIPTION & USE

**Armstead Trade** Wood Primer is a professional quality, solvent-based wood primer with excellent adhesion properties providing an ideal surface for **Armstead Trade** Undercoat. Suitable for both interior and exterior use.

## KEY BENEFITS

- **Primes for undercoating**
- **Excellent adhesion**
- **For interior & exterior wood**

## PACK SIZES



## COLOUR RANGE

White only.

## COMPOSITION (NOMINAL)

<b>Pigment:</b>	Lightfast Pigments.
<b>Binder:</b>	Oil Modified Alkyd.
<b>Solvent:</b>	White Spirit.

## VOLUME SOLIDS

61% (nominal).

## SURFACE PREPARATION

Surfaces must be clean, dry, free from all defective or poorly adhering material, dirt, grease, wax etc.

Thoroughly rub down previously painted surfaces, using 'wet flattening' methods where possible, then wipe off with a damp, lint free cloth.

Treat any knots in wood with an appropriate knotting solution. Any surface defects must be filled with a suitable filler.

**Note:** Special precautions should be taken during surface preparation of pre-1960s paint surfaces over wood and metal as they may contain harmful lead.

## APPLICATION



Brush only. For Health and Safety reasons related to all solvent-based paints, spray application is not recommended.

As with other solvent-based paints, do not apply in temperatures below 5°C (as recommended by British Standard BS 6150).

## SYSTEM INFORMATION

Stir thoroughly before use.

After suitable surface preparation, apply 1 coat of **Armstead Trade** Wood Primer to all bare wood and allow to dry. Finish with an appropriate **Armstead Trade** paint system.

## PRACTICAL COVERAGE



A guide to the practical coverage which can be achieved under normal conditions is up to 13m<sup>2</sup>/litre.

## DRYING TIMES (SINGLE COAT, STANDARD THICKNESS)



**Touch Dry:** 4-6 hours\*  
**Recoat:** 16-24 hours\*

\* Dependent upon temperature & humidity

## CLEANING UP



After use, remove as much paint as possible from brushes before cleaning with white spirit.

## TRANSPORTATION & STORAGE

Do not use or store in extremes of temperature and protect from frost. To prevent spillage, please store and transport upright.

## VOC

EU limit value for this product (cat A/g): 350g/l (2010) This product contains max. 300g/l VOC.

VOC Content High 25% - 50%. VOCs (Volatile Organic Compounds) contribute to atmospheric pollution.

## FURTHER SUPPORT

Online: [www.armsteadtrade.co.uk](http://www.armsteadtrade.co.uk)  
Email: [armstead.advice@akzonobel.com](mailto:armstead.advice@akzonobel.com)  
Phone: 0333-222-70-70

Please visit [www.armsteadtrade.co.uk](http://www.armsteadtrade.co.uk) to download safety sheet SDSAM102



Like us on Facebook



Videos on YouTube



Follow us on Twitter



Let's create together a better future for our planet.  
Find out how at: [www.armsteadtrade.co.uk/pp](http://www.armsteadtrade.co.uk/pp)