

D 400**Access Covers****ULTRA™ Specification**

KD12-6



KD19

Features:

- Manufactured to BS EN 124 class D 400
- BSI Kitemarked for third party assurance of quality
- ULTRA™ products comply with HA 104
- ULTRA™ products comply with BS 7903
- Suitable for carriageways and fast moving traffic
- AMP™ patented anti-movement technology frames
- Non-rock three point suspension for stability and silent operation
- Ductile iron to ISO 1083 for improved weight to strength ratio
- Black coated finish

Options:

- Standard Locking
- High Security Locking
- Badging e.g. FW, SW, Motorway Comms
- Sealing Plates
- Pressure Plates (150 mm Deep Products Only)
- Ventilation
- Safety Grids
- Security Plates

Standard Sizes

Code	Clear Opening (mm)	O/all Frame (mm)	Frame Depth (mm)	Weight (kg)	D/Tri Lids
KD10	600 x 600	752 x 752	100	77	1
KD10-6	600 x 600	752 x 752	150	82	1
KD10CH-U	600 dia	800 x 800	100	58	-
KD12	675 x 675	827 x 827	100	84	1
KD12-6	675 x 675	827 x 827	150	98	1
KD14	750 x 600	900 x 750	100	95	1
KD14-6	750 x 600	900 x 750	150	105	1
KD15	750 x 750	900 x 900	100	105	1
KD15-6	750 x 750	900 x 900	150	115	1
KD16	900 x 600	1050 x 750	100	115	1
KD16-6	900 x 600	1050 x 750	150	124	1
KD17	900 x 900	1050 x 1050	100	190	1
KD17-6	900 x 900	1050 x 1050	150	265	1
KD18-6	1000 x 1000	1160 x 1160	150	241	1
KD19	1220 x 675	1370 x 825	100	160	2
KD19-6	1220 x 675	1370 x 825	150	170	2
KD20-6	1830 x 675	1980 x 825	150	340	3
KD21	1200 x 900	1360 x 1060	100	250	2
KD21-6	1200 x 900	1350 x 1060	150	290	2
KD22-6	900 x 750	1060 x 910	150	197	2